


**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Paint  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:** Maston Oy  
Teollisuustie 10  
FI 02880 Veikkola - Finland  
Phone.: +358 20 7188 580 -  
Fax: +358 20 7188 599  
maston@maston.fi  
www.maston.fi
- 1.4 Emergency telephone number:** Myrkytystietokeskus (Giftinformationcentralen) PL 340  
00029 HUS FINLAND +358(0)9471977

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) n° 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.  
Aerosol 1: Pressurised container: May burst if heated., H229  
Aerosol 1: Flammable aerosols, Category 1, H222  
Eye Irrit. 2: Eye irritation, Category 2, H319  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**CLP Regulation (EC) n° 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
Aerosol 1: H229 - Pressurised container: May burst if heated  
Aerosol 1: H222 - Extremely flammable aerosol  
Eye Irrit. 2: H319 - Causes serious eye irritation  
STOT SE 3: H336 - May cause drowsiness or dizziness
- Precautionary statements:**  
P102: Keep out of reach of children  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211: Do not spray on an open flame or other ignition source  
P251: Do not pierce or burn, even after use  
P260: Do not breathe dust/fume/gas/mist/vapours/spray  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking
- Substances that contribute to the classification**  
Acetone; Butyl Acetate
- 2.3 Other hazards:**  
Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

- 3.1 Substance:**  
Non-applicable
- 3.2 Mixture:**

- CONTINUED ON NEXT PAGE -









**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continue)**

**Chemical description:** Aerosol

**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	<b>Acetone</b> ATP CLP00		25 - <50 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger 	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX	<b>Butane</b> ATP CLP00		15 - <20 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger 	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX	<b>Propane</b> ATP CLP00		10 - <15 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger 	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>Butyl Acetate</b> ATP CLP00		5 - <10 %
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning 	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene (mixture of isomers)</b> ATP CLP00		5 - <10 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning 	
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene</b> ATP ATP06		1 - <5 %
	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger 	
CAS: 78-83-1 EC: 201-148-0 Index: 603-108-00-1 REACH: 01-2119484609-23-XXXX	<b>Isobutanol</b> ATP CLP00		0,25 - <1 %
	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger 	
CAS: 96-29-7 EC: 202-496-6 Index: 616-014-00-0 REACH: 01-2119539477-28-XXXX	<b>Butanone oxime</b> ATP CLP00		<0,05 %
	Regulation 1272/2008	Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger 	

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

### Maston - Heatresistant spray paint - Kuumankestomaali Spray 400121, 400805, 400996, 710221, 710222

#### SECTION 4: FIRST AID MEASURES (continue)

Non-applicable

#### SECTION 5: FIREFIGHTING MEASURES

##### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

##### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

##### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

##### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

##### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

##### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

##### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

##### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

##### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid projections and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

- CONTINUED ON NEXT PAGE -

**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222**

**SECTION 7: HANDLING AND STORAGE (continue)**

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C  
 Maximum Temp.: 50 °C  
 Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
	IOELV (8h)	IOELV (STEL)	Year
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	50 ppm	221 mg/m <sup>3</sup>	2014
	100 ppm	442 mg/m <sup>3</sup>	
	Year		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	100 ppm	442 mg/m <sup>3</sup>	2014
	200 ppm	884 mg/m <sup>3</sup>	
	Year		
Acetone CAS: 67-64-1 EC: 200-662-2	500 ppm	1210 mg/m <sup>3</sup>	2014
	Year		

**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the professional exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Ocular and facial protection

Non-applicable

E.- Bodily protection

Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 90,05 % weight  
 V.O.C. density at 20 °C: 640,29 kg/m<sup>3</sup> (640,29 g/L)  
 Average carbon number: 4,14  
 Average molecular weight: 72,8 g/mol

- CONTINUED ON NEXT PAGE -

**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222****SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Aerosol
Appearance:	Not available
Color:	Not available
Odor:	Not available

**Volatility:**

Boiling point at atmospheric pressure:	-1 °C (Propellant)
Vapour pressure at 20 °C:	359970 Pa
Vapour pressure at 50 °C:	769937 Pa (770 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	711 kg/m <sup>3</sup>
Relative density at 20 °C:	0,711
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	359970 Pa (3,6 bar)

**Flammability:**

Flash Point:	-60 °C (Propellant)
Autoignition temperature:	365 °C (Propellant)
Lower flammability limit:	0,8 % Volume
Upper flammability limit:	12 % Volume

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity:**

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

### Maston - Heatresistant spray paint - Kuumankestomaali Spray 400121, 400805, 400996, 710221, 710222

#### SECTION 10: STABILITY AND REACTIVITY (continue)

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Avoid direct impact	Not applicable	Not applicable

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### SECTION 11: TOXICOLOGICAL INFORMATION

##### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

##### A.- Ingestion:

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

##### B- Inhalation:

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

##### C- Contact with the skin and the eyes:

- Contact with the skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

##### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensibilizing effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensibilizing effects. For more information see section 3.

##### F- Specific target organ toxicity (STOT)-time exposure:

Exposure in high concentrations can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of concentration.

##### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

##### H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -

**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
 400121, 400805, 400996, 710221, 710222**
**SECTION 11: TOXICOLOGICAL INFORMATION (continue)**
**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h)	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
Butane CAS: 106-97-8 EC: 203-448-7	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	658 mg/L (4 h)	Rat
Isobutanol CAS: 78-83-1 EC: 201-148-0	LD50 oral	3350 mg/kg	Rat
	LD50 dermal	2460 mg/kg	Rabbit
	LC50 inhalation	24,6 mg/L (4 h)	Rat
Butanone oxime CAS: 96-29-7 EC: 202-496-6	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Non-applicable	

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity		Specie	Genus
Acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	23,5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LC50	13,5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0,6 mg/L (96 h)	Gammarus lacustris	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Isobutanol CAS: 78-83-1 EC: 201-148-0	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
Butanone oxime CAS: 96-29-7 EC: 202-496-6	LC50	843 mg/L (96 h)	Pimephales promelas	Fish
	EC50	750 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	83 mg/L (72 h)	Scenedesmus subspicatus	Algae

**12.2 Persistence and degradability:**

- CONTINUED ON NEXT PAGE -

**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
 400121, 400805, 400996, 710221, 710222**
**SECTION 12: ECOLOGICAL INFORMATION (continue)**

Identification	Degradability		Biodegradability	
Acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.96	% Biodegradable	96 %
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
Isobutanol CAS: 78-83-1 EC: 201-148-0	BOD5	0.4 g O2/g	Concentration	100 mg/L
	COD	2.41 g O2/g	Period	14 days
	BOD5/COD	0.17	% Biodegradable	90 %
Butanone oxime CAS: 96-29-7 EC: 202-496-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	24 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0,24
	Potential	Low
Butane CAS: 106-97-8 EC: 203-448-7	BCF	33
	Pow Log	2,89
	Potential	Moderate
Propane CAS: 74-98-6 EC: 200-827-9	BCF	13
	Pow Log	2,86
	Potential	Low
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1,78
	Potential	Low
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2,77
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3,15
	Potential	Low
Isobutanol CAS: 78-83-1 EC: 201-148-0	BCF	3
	Pow Log	0,76
	Potential	Low
Butanone oxime CAS: 96-29-7 EC: 202-496-6	BCF	5
	Pow Log	0,59
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,929E+0 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	23040 N/m (25 °C)	Moist soil	Yes
Butane CAS: 106-97-8 EC: 203-448-7	Koc	900	Henry	9,626E+4 Pa·m <sup>3</sup> /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	11870 N/m (25 °C)	Moist soil	Yes
Propane CAS: 74-98-6 EC: 200-827-9	Koc	460	Henry	7,164E+4 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	7020 N/m (25 °C)	Moist soil	Yes

- CONTINUED ON NEXT PAGE -



**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222**

**SECTION 12: ECOLOGICAL INFORMATION (continue)**

Identification	Absorption/desorption		Volatility	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	24780 N/m (25 °C)	Moist soil	Non-applicable
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	5,249E+2 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	7,984E+2 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	28590 N/m (25 °C)	Moist soil	Yes
Isobutanol CAS: 78-83-1 EC: 201-148-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	23780 N/m (25 °C)	Moist soil	Non-applicable
Butanone oxime CAS: 96-29-7 EC: 202-496-6	Koc	3	Henry	Non-applicable
	Conclusion	Very High	Dry soil	Non-applicable
	Surface tension	25700 N/m (25 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	Gases in pressure containers (including halons) containing dangerous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2015 and RID 2015:

**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222****SECTION 14: TRANSPORT INFORMATION (continue)**

- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
 Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Dangerous for the environment:** No  
**14.6 Special precautions for user**  
 Special regulations: 190, 327, 625  
 Tunnel restriction code: D  
 Physico-Chemical properties: see section 9  
 Limited quantities: 1 L  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 37-14:



- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
 Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Dangerous for the environment:** No  
**14.6 Special precautions for user**  
 Special regulations: Non-applicable  
 EmS Codes: F-D, S-U  
 Physico-Chemical properties: see section 9  
 Limited quantities: 1 L  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2015:



- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
 Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Dangerous for the environment:** No  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

- CONTINUED ON NEXT PAGE -

**Maston - Heatresistant spray paint - Kuumankestomaali Spray  
400121, 400805, 400996, 710221, 710222****SECTION 15: REGULATORY INFORMATION (continue)****Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):**

Non-applicable

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION****Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

**Modifications related to the previous security card which concerns the ways of managing risks. :**

Content of the 3rd section presenting modifications:

- Ethylbenzene (100-41-4): R Phrases, Hazard statements

**Texts of the legislative phrases mentioned in section 2:**

H336: May cause drowsiness or dizziness

H229: Pressurised container: May burst if heated

H222: Extremely flammable aerosol

H319: Causes serious eye irritation

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) n° 1272/2008:**

Acute Tox. 4: H312 - Harmful in contact with skin

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Carc. 2: H351 - Suspected of causing cancer

Eye Dam. 1: H318 - Causes serious eye damage

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Gas 1: H220 - Extremely flammable gas

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Press. Gas: H280 - Contains gas under pressure, may explode if heated

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

STOT SE 3: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Eye Irrit. 2: Calculation method

**Advice related to training:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

### Maston - Heatresistant spray paint - Kuumankestomaali Spray 400121, 400805, 400996, 710221, 710222

#### SECTION 16: OTHER INFORMATION (continue)

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://esis.jrc.ec.europa.eu>

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

- ADR: European agreement concerning the international carriage of dangerous goods by road
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol–water partition coefficient
- Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -