www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

# SAFETY DATA SHEET PENOSIL Gold Gun 65

Date: 16.06.2010 Version nr.: 4 Revised: 30.08.2011

### 1. Identification of the mixture and of the company/undertaking

1.1. Product identifier: PENOSIL Gold Gun 65

### 1.2. Relevant identified uses of the mixture and uses advised against:

Foam is used for installation of doors and windows, insulation and fixation of tubes, filling of holes and gaps, fixation of wall panels and roof stones, and for thermal insulation.

Adheres well to most building materials, with the exception of teflon, polyethylene and silicon surfaces. Cured foam is sensitive to UV-light and direct sunlight.

1.3. Details of supplier of the safety data sheet:

Krimelte Ltd 13619 Tallinn Suur-Paala 10 Estonia Tel. +372 605 93 00 Fax: (+372) 605 93 15 112

**1.4. Emergency telephone number:** 

### 2. Hazards identification

2.1. Classification of the mixture According to 67/548/EC





Extremely flammable (F+)

R12 Extremely flammable R20 Harmful by inhalation

R36/37/38 Irritating to eyes, respiratory system and skin

R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitization by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

### Health

Fire

Environment

The vapor will irritate throat and lungs. Vapor is dangerous in huge amounts. Irritating to eyes. Occasionally, contact produces skin allergy. May cause long-term adverse effects in the aquatic environment. The propellant is inflammable and explosive.

### 2.2. Label elements

- 1. Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- 2. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- 3. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

2.2.1 Hazard symbol:



Harmful (Xn) 2.2.2 Hazardous ingredients: SAFETY DATA SHEET **PENOSIL Gold Gun 65** 



Extremely flammable (F+) Consists isocyanate. See information applied by the manufacturer.

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

### SAFETY DATA SHEET **PENOSIL Gold Gun 65**

2.2.3 R-phrases	R12 R20 R36/37/38 R40 R42/43 R48/20	Extremely flammable Harmful by inhalation Irritating to eyes, respiratory system and skin Limited evidence of a carcinogenic effect May cause sensitization by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation
2.2.4 S-phrases	S2 S9 S16 S 23 S33 S36/37 S45 S51	Keep out of the reach of children Keep container in a well-ventilated place Keep away from sources of ignition No smoking Do not breathe gas/vapor Take precautionary measures against static discharges. Wear suitable protective clothing and gloves In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Use only in well-ventilated areas
2.3. Other hazards	No data ava	ailable.

#### 3.Composition/information on ingredients 3.1. Substances, Classification of substances

CAS-nr.	Chemical name	Conte	nt	Classification		
		Max.		According Directive 67/548/EEC	According Regulation 1272/2008 (CLP)	
9016-87-9	Diphenylmethane-4´,4 ´-diisocyanate	40	%	Xn; R20 R36/37/38 R42/43 R40 R48/20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2, H319 Resp. Sens. 1; H334 Skin Sens.1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	
75-28-5	Isobutane	8	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280	
74-98-6	Propane	4	%	F+; R12	Flam. Gas 1; H220 Press. Gas; H280	
115-10-6	Dimethylether	4	%	F+; R12	Flam. Gas 1; H220 Press. Gas H280	

### 4. First aid measures

### 4.1 Description of first aid measures

Inhalation:	Move the exposed person to fresh air. Seek medical attention.
Skin contact:	Wash off with plenty of soap and water. Remove contaminated clothing.
	Seek medical attention if irritation or symptoms persist.
Contact with eyes:	Rinse eyes immediately with plenty of water, keeping the eye open.
	Seek medical attention.
Ingestion:	Do not induce vomiting or give water to drink. Seek medical attention
	and show product label.
4.2. Most important symptor	ns and effects, both acute and delayed
Inhalation	Irritating to respiratory system.
<b>A I I I</b>	

Skin contact Irritating to skin.

#### www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

### SAFETY DATA SHEET **PENOSIL Gold Gun 65**

Contact with eyes Ingestion

Irritating to eyes

May cause suffocation and vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

As a general rule, and in all cases of doubt or when symptoms persist, always seek medical attention.

### 5. Fire fighting measures

### 5.1 Extinguishing media

5.1.1. Suitable extinguishing media:

Use extinguishing media appropriate the surrounding fire conditions. Use as appropriate: water spray, dry extinguishing media, foam and carbon dioxide. No specific recommendations.

#### 5.1.2 Unsuitable extinguishing media: 5.2. Special hazards arising from the mixture

Due to heat pressure in the aerosol-can is rising and there is a risk for explosion. In contact with fire product forms toxic fumes. Explosive propellant-air mix can be formed. 5.3. Advice for fire-fighters

No specific recommendations.

### 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear protective clothing, goggles and protective chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Avoid contact with skin and eyes. Do not inhale fumes. Use a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387), when you use product in the room which has a poor ventilation

### 6.2 Environmental precautions:

Spillages shall be absorbed by sand or cloths and stored in suitable container, or allow the foam to solidify. The waste must be handled in accordance with legal requirements.

#### 6.3 Methods and material for containment and cleaning up

Fresh foam can be removed with acetone, cured foam only mechanically.

### 7. Handling and storage

### 7.1 Precaution for safe handling:

During operation, note that the product contains a flammable gas. Keep away from heat. Do not break or burn even after use. Should not be sprayed on a open flame or any incandescent material. 7.1.1. Protective measures

Ensure good ventilation. Keep away from heat. Keep away from sources of ignition- No smoking. Avoid contact with eyes and skin. Avoid static electricity. Make use of protective goggles and protective chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms.

### 7.1.2. Advice on general occupational hygiene

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep in a cool, dry, well-ventilated area in an upright position away from direct sunlight and other heat sources. Do not store in the direct sunlight and not more than +50 °C. Storage: temperature +5°C to +30 °C.

### 7.3. Specific end use(s)

Foam is used for installation of doors and windows, insulation and fixation of tubes, filling of holes and gaps, fixation of wall panels and roof stones, and for thermal insulation. Adheres well to most building materials, with the exception of teflon, polyethylene and silicon surfaces. Cured foam is sensitive to UVlight and direct sunlight.

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

# SAFETY DATA SHEET PENOSIL Gold Gun 65

### 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit value

Components	CAS-No.	Type form of exposure	Control parameters	
Dimethyl ether	115-10-6	TWA	1920 mg/m <sup>3</sup>	
			1000 ppm	
Diphenylmethane-	9016-87-9	No information	0,05 mg/m <sup>3</sup> 8 hours	
4',4'-diisocyanate			0.005 ppm 8 hours	
Propane	74-98-6 No information Short time: 2000 mg/m <sup>3</sup> , 1100 ppm		Short time: 2000 mg/m <sup>3</sup> , 1100 ppm	
-			Long time: 1500 mg/m <sup>3</sup> , 800 ppm	
Butane	106-97-8	No information	Short time: 1810 mg/m <sup>3</sup> , 750 ppm	
			Long time: 1450 mg/m <sup>3</sup> , 600 ppm	

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

8.2.2. Individual protection measures, such as personal protective equipment

 Eye/face protection:
 During the work make use of protective goggles

 Skin protection:
 During the work make use of protective chemical resistant gloves

 classified under Standard EN374: protective gloves against chemicals and microorganisms.

 Respiratory protection:
 Use the product only in well-ventilated rooms. Do not inhale fumes.

 When using in poorly ventilated area, wear a suitable filter of the mask (ie type A1 in accordance with EN 14387).

8.2.3. Environmental exposure controls Do not let into environment. May cause long-term adverse effects in the aquatic environment.

### 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Pale beige
Odour	Characteristic
рН	Not applicable
Melting point / freezing point	Not relevant
Boiling point	Over +100 °C
Flash point	Below -20 °C
Evaporation rate	Not relevant
Flammability	Above +100 °C
Explosion limits	Low: 2 % vol, high: 10% vol.
Vapor pressure	5 Bar/+20 °C 10 Bar/+50 °C
Vapor density	Not applicable
Relative density	1.1 g/ml/+20 °C
Solubility in water	insoluble
Solubility in other solvents	In acetone soluble
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	+ 200 °C
Viscosity	ca 500 cP/+20 °C
Explosive properties	Contains flammable gases.
Oxidizing properties	Not applicable
Other information	Lack of data

9.2.

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET PENOSIL Gold Gun 65

### **10. Stability and reactivity**

10.1. Reactivity
 The mixture is not reactive under recommended storage and handling conditions (see section 7).
 10.2. Chemical stability
 The mixture is stable under recommended storage and handling

conditions (see section 7). **10.3. Possibility of hazardous reactions** In case of fire, the product can create corrosive and hazard

gases.

**10.4 Conditions to avoid:** An aerosol container is under pressure, do not expose to heat. Do not store in the sun, and not more than +50 °C. Do not break or burn even after use. Should not be sprayed on a open flame, or any incandescent material.

10.5. Incompatible materials: No data available

**10.6. Hazardous decomposition products:** In case of fire, the product can create corrosive and hazard gases.

### 11. Toxicological information

- 11.1. Information on toxicological effects
- 11.1.1. Substances

11.1.1.1. The relevant hazard classes for which information shall be provided are:

(a) Acute toxicity				
	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane	
Acute Oral toxicity	Not applicable	LD50 (rat): > 2.000 mg/kg	Not applicable	
Acute Dermal toxicity	Not applicable	Not applicable	Not applicable	
Acute Inhalation toxicity	LC50 (rat): 164 000 ppm Respiratory effects Anaesthetic effects Central nervous system depression narcosis Cardiac irregularities Coma.	LC50 (rat): 490 mg/m <sup>3</sup> 4h Tested substance: Aerosol Saturated vapour concentration at 25 °C: 0,09 mg/m <sup>3</sup>	Not applicable	

### (b) Skin corrosion / irritation

	Dimethyl ether	Diphenylmethane-4´,4	Isobutane /
		´-diisocyanate	propane
Skin	Not tested on animals	Rabbit	No skin
irritation	Classification: Not classified as irritant	Result: No skin irritation	irritation
	Result: No skin irritation	Method: OECD test	
	Not expected to cause skin irritation based on	guide 404	
	expert review of the properties of the substance.	-	

### (c) Serious eye damage / irritation

	Dimethyl ether	Diphenylmethane-4',4	Isobutane /
		´-diisocyanate	propane
Eye	Not tested on animals	Rabbit	No eye
irritation	Classification: Not classified as irritant	Result: No eye irritation	irritation
	Result: No eye irritation	Method: OECD test	
	Not expected to cause eye irritation based on	guide 405	
	expert review of the properties of the substance.		

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

# SAFETY DATA SHEET PENOSIL Gold Gun 65

(d) Respiratory or skin sensitization

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Sensitization	Not tested on animals Classification: Not a skin sensitizer Not expected to cause eye irritation based on expert review of the properties of the substance.	Result: May cause sensitization by inhalation and skin contact Isocyanate vapor may cause asthmatic allergy	No sensitization effect

### (e) Germ cell mutagenicity

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Germ cell mutagenicity	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.	Lack of data	Not applicable

### (f) Carcinogenicity

	Dimethyl ether	Diphenylmethane-4´,4 ´-diisocyanate	Isobutane / propane
Carcinogenicity	Animal testing did not show any carcinogenic effects.	Lack of data	Not applicable

### (g) Reproductive toxicity

	Dimethyl ether	Diphenylmethane-4 ´,4´-diisocyanate	Isobutane / propane
Reproductive toxicity	No toxicity on reproduction May cause cardiac arrhythmia. Rapid evaporation of the liguid may cause frostbite.	Lack of data	Not applicable
	evaporation of the liquid may cause hostblie.		

(h) STOT-single exposure
Lack of data
(i) STOT-repeated exposure
Lack of data

### 12. Ecological information

12.1. Toxicity

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Toxicity to fish	LC50 /96h/ Poecilia reticulate (guppy): > 4000 mg/l	LC50 /96h/ danio rerio: > 1.000 mg/l Method: OECD test guide 203	Not applicable
Toxicity to aquatic invertebrates	EC50 /48h/ Daphnia: > 4000 mg/l LC50 /48h/ Daphnia: 755,5 mg/l	EC50 /24h/ Daphnia magna: > 1.000 mg/l Method: OECD test guide 202	Not applicable
Chronic toxicity to fish	Due to its physical properties, there is no potential for adverse effects.	Lack of data	Lack of data
Toxicity to bacteria	Lack of data	EC50 /3h/ activated sludge: >100 mg/l Method: OECD test guide 209	Lack of data

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

### SAFETY DATA SHEET **PENOSIL Gold Gun 65**

### 12.2. Persistence and degradability

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Persistence and degradability	Method: Closed Bottle test According to the results of tests of biodegradability this product is not readily biodegradable.	Biodegradability 28 days 0 %. Method: OECD test guide 302 C	Not applicable

#### 12.3. Bio-accumulative potential:

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Bioaccumulation	No data available	No data available	Not applicable

#### 12.4. Mobility in soil:

	Dimethyl ether	Diphenylmethane-4´,4´- diisocyanate	Isobutane / propane
Mobility in soi	I Koc: 7,759	No data available	Not applicable

### 12.5. Results of PBT and vPvB assessment:

	Dimethyl ether	Diphenylmethane-	Isobutane /
		4´,4´-diisocyanate	propane
PBT and	This substance is not considered to be persistent,	No data available	Not
vPvB	bio accumulating nor toxic (PBT). The substance is		applicable
assessment	not considered to be very persistent nor very bio		
	accumulating (vPvB).		

### 12.6. Other adverse effects

Dimethyl ether	Diphenylmethane-4´,4	Isobutane / propane
	´-diisocyanate	
Ozone depletion potential: 0	Not applicable	Not applicable
Global warming potential (GWP): 1		

### 13. Disposal considerations

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal: The product and packages must be handled in accordance with national and local requirements.

13.1.2. Waste treatment options: 13.2. Additional information

Foam bottles are recyclable.

No specific recommendations.

### 14. Transport information

- 14.1 UN number
- 14.2 Packing Group
- 14.3 Road ADR
- 14.4 Railway RID
- 14.5 Transport by sea GGVSee/IMDG-Code 14.6 Air transport ICAO-TI/IATA-DGR

1950 Not known Inflammable aerosol Class 2/5F Inflammable aerosol Class 2/5F Aerosol Class 2

### 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET **PENOSIL Gold Gun 65** 

www.penosil.com

Krimelte Ltd Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

## SAFETY DATA SHEET PENOSIL Gold Gun 65

### Not applicable

### 15.2. Chemical safety assessment

Chemical safety assessment has been carried out for dimethyl ether and still at work for diphenylmethane-4',4'-diisocyanate.

### 16. Other information

16.1. Date of preparation of the latest version of the SDS Written in the beginning of the safety data sheet. 16.2. Abbreviations and acronyms TWA: Time Weighted Average LC50: Lethal Concentration Medium EC50: effective Concentration Medium STOT: Specific target organ toxicity PBT: Persistent, bioaccumulativ and toxic vPvB: very persistent very bioaccumulative Acute Tox.4: Acute Toxicity: inhaled- Category 4 Carc. 2: Carcinogenicity- Category 2 Eye Irrit. 2: Serious eye damage/ eye irritation- Category 2 Resp. Sens. 1: Respiratory sensitization- Category 1 Skin Irrit.2: Skin corrosion/irritation- Category 2 Skin Sens. 1: Skin sensitization- Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure): inhalation- Category 2 STOT SE 3: Specific target organ toxicity (single exposure): inhalation- Category 3 Flam. Gas 1: Flammable Gas- category 1 Press. Gas: Gases under pressure 16.3. Key literature references and sources of data The safety data sheet meets the requirements of the European Parliament and Council Regulation (EC) No.1907/2006 and the Chemicals Act of the Republic of Estonia and regulation No 130 of Minister of Social Affairs. 16.4. Classification and classification procedure used for mixtures 16.5. Relevant R-phrases and/or H-statements (specified in clause 3) According Directive 67/548/EEC R12 Extremely flammable R20 Harmful by inhalation. R36/37/38 Irritating to eyes, respiratory system and skin. R40 Limited evidence of a carcinogenic effect R42/43 May cause sensitization by inhalation and skin contact. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. According Regulation 1272/2008 (CLP) H220 Extremely flammable gas H280 Contains gas under pressure; may explode if heated H315 Cause skin irritation H317 May cause an allergic skin reaction H319 Causes serious eve irritation H332 Harmful if inhaled H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled H335 May cause respiratory irritation H351 Suspected of causing cancer H373 May cause damage to organs through prolonged or repeated exposure if ihaled. 16.6. Training advice No specific recommendations.

### 16.7. Further information

No specific recommendations.